



Airrex AF-2300 is perfect solution with Airrex ADH-8000 in restoration against flood.



• Low noise



• 7blade



• stackable



 Powerful air flow



Robust design



 Light weight (25.4lbs)



Socket on top



Non-slip rubber



Certification






AF-2300 Specifications

ITEMS	Fan
Power supply	115Vac 60Hz 1Ph
Current consumption	HIGH: 1.4A / LOW: 1.13A
Fan type	Axial Fan
Fan Blade	16 inch Dia. / 7 blade / Integral
Noise	HIGH: 62.5dB / LOW: 54.2dB
Weight	25.4 lbs
Power Socket	Υ
Air Flow	HIGH: 1,932CFM(54.7CMM) LOW: 1,417CFM(40.1CMM)
Dimesions (WxDxH)	20 x 22 x 15.7 inches
Case	Roto-mold Housing
Certification	ETL/ CSA



Stackable example



🕱 Designs and specifications of products are subject to change without prior notice for the improvements. The colors of products may be different due to the printing process.









Looking for an airmover that offers 4 different positions to help you tackle the most difficult drying challenges? Looking for the most CFM per circuit of any airmover on the market? it's called the AF-2300.





TEL: 888-535-8841

FAX: 469-574-7924



E-mail: sales@airrexusa.com **Website:** www.airrexusa.com

- Very low ampere draw
- 4 position versatility for handling a wide range of applications
- Dry structures fast with 1932 actual CFM

- Turn or tilt on non-slip rubber foot to switch operating positions
- Compact design that's stackable for operation and storage
- Ideal for structural drying, carpet cleaning, ventilation