

## Paint "N" Peel Fireplace Cleaner

### MANUFACTURER

SaverSystems  
Richmond, IN 47374  
800-860-6327  
Fax 765-935-4999  
www.chimneysaver.com

### DESCRIPTION

ChimneySaver Paint "N" Peel Fireplace Cleaner is a water-based cleaning poultice that removes unsightly smoke, soot, creosote and dirt stains from masonry fireplace fronts and hearths. No additional water is needed for application or removal. Simply paint the product on the surface, allow it to dry, and then peel it off.

### USES

Product can be used to clean most all masonry surfaces both interior/exterior, textured or smooth brick, stone, marble, granite, slate, tile, concrete, mortar and limestone. Always test for compatibility and desired results with your specific surface before proceeding with entire project. Apply product in a small inconspicuous "test" area, allow product to dry completely (4- 12 hours) before removing. Heavily soiled areas may require multiple applications.

### BENEFITS

- Restores masonry to its original appearance
- Waterless - simply paint on and peel off
- Environmentally Friendly - No harsh chemicals
- Works on nearly all masonry surfaces

### DIRECTIONS FOR USE

Do not thin product. Apply when surface and air temperatures are between 45° F and 95° F.

**Preparation:** Wipe surface with a dry or slightly damp rag to remove dust. Mask off work areas and cover all non-target surfaces with plastic or dropcloths. The use of removable painters tape is recommended to protect surfaces adjacent to product application, such as fireplace glass doors, fireplace mantles and any trim that abuts the masonry to which product is to be applied. Be sure to protect all surrounding carpet, fabric, metal, wood, and painted surfaces from inadvertent spills and roller splatter, as product may cause stains or damage to non-target surfaces. For best results, surfaces to which product is to be applied should be dust free, dry, and cool to touch before application. Do not apply while fireplace is in use.

### APPLICATION

Stir before use. Apply a thick, liberal coat, approximately 1/8" – 3/16" thickness using a paint brush and/or a thick nap roller. Be sure to maintain the recommended

thickness across the entire surface area to be coated and near the edges of your project. Ensuring an even application will help the product peel off easily and uniformly when dry.

For areas that are more heavily soiled, agitation with a stiff nylon bristle scrub brush may be required to help the product work deeper into the surface. Once surface has been agitated, recoat to be sure a thick, even application of product remains on surface.

On extremely porous surfaces or in extremely dry conditions, it may be beneficial to lightly mist the surface with water, agitate with a soft bristle brush and blot dry with clean rags just prior to application to help prevent product from drying out too quickly.

**Coverage:** When applied at 1/8"-3/16" thickness, product will cover 40 - 80 sq. ft. per gallon depending on the texture and density of the surface.

**Cleanup:** Wipe excess material off of tools. Tools may then be cleaned with soap and water. Dispose of dried coating in accordance with local regulations for non-hazardous solid waste. Absorb small spills with inert material and dispose of according to local regulations. Rinse spill area with water.

**Dry Time:** At 1/8"-3/16" thickness, product will take 4-12 hours to dry completely depending on environmental conditions.

**Removal of Dry Product:** Product must be completely dry before removing. Starting at an edge, pull the dry film off slowly at an angle with both hands. Be careful not to tear the coating as this may make it more difficult to remove. Once film is completely removed, fireplace can be put back in use.

### Safety and Handling:

The use of protective gloves and chemical splash goggles are recommended when handling any chemical product. Wash thoroughly after handling. For additional information, consult the MSDS for this product available online at [www.chimneysaver.com](http://www.chimneysaver.com).

### CAUTIONS

**Keep out of reach of children.** Do not take internally. Close container after each use. Do not reuse containers. The use of protective gloves and eye wear is recommended to avoid contact with skin and eyes.

**First Aid:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash with soap and

water. If swallowed, do not induce vomiting. Drink two glasses of water. Get medical attention immediately. For additional information consult MSDS for this product.

### LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to the results is offered, expressed or implied. SaverSystems warrants this product to be free from defects. SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product has been applied. This warranty does not include the cost of labor for application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages so this limitation or exclusion may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

### PACKAGING

ChimneySaver Paint "N" Peel Fireplace cleaner is available in 1 gallon recyclable plastic containers.

### TRANSPORT AND STORAGE

ChimneySaver Paint "N" Peel fireplace cleaner is not considered hazardous under Department of Transportation (DOT) regulations. Store in a cool, dry, well ventilated place. Do not stack pallets.

**Keep from freezing.**

### PHYSICAL PROPERTIES

COLOR . . . . . Light gray, thick paste  
COMPOSITION . . . . . Proprietary blend of water miscible polymers and surfactants.  
FLASH POINT . . . . . None  
WEIGHT . . . . . (8 #/gallon)  
VOC CONTENT (ASTM D 6886) . . . . . 41 g/L  
SHELF LIFE. . . . . 12-18 months in unopened container