

Innsbrook Traditional & Loft Contemporary Vent-Free Fireplace Inserts

Traditional 28,000 BTU Vent-Free Fireplace Insert shown with Matte Black Surround.



Vent-Free Fireplace Inserts



Standard Features

We offer Vent-Free Inserts in two sizes (20,000 BTUs and 28,000 BTUs) and in two styles (traditional and contemporary) – so you are sure to find one to fit your existing wood-burning fireplace.

A 10,000 BTUs contemporary system is available for bedroom applications - where allowed by codes.

Our Innsbrook Vent-Free inserts feature Banded Brick Liners, with hand-painted ceramic fiber logs on a variableflame burner. The unique Slope Glaze Burner produces natural flickering flames.

The Loft Series Vent-Free Insert features a contemporary linear burner in a sleek, black firebox that reflects the flames to create depth and visual interest.

A fine mesh barrier screen comes standard with all models.

Control Options

Your Innsbrook or Loft fireplace insert lights at the flick of a switch to produce consistent, reliable heat, even when electric power fails. Add the convenience of an optional thermostat, wireless wall thermostat, remote control, or thermostat remote control, and enjoy all the comfort of a warm fire without the mess and hassle.

Your Remote-Ready Millivolt Innsbrook or Loft Insert works with any of our battery operated Thermostat Remote Controls, or connects to a simple wall switch or wall thermostat.

The Intermittent Pilot models save even more energy by eliminating the standing pilot – yet can still operate in a power outage with a battery backup.

Surrounds & Shrouds

Your new Vent-Free insert will require a surround kit to conceal the original fireplace opening. For Innsbrook and Loft models, choose one of our steel surrounds with either 7-inch top and 6-inch side panels, or 4-inch top and 3-inch side panels. Innsbrook models also have the option of an old-world style three-piece cast iron surround.

For installations where your insert does not rest on the hearth, we offer optional custom metal surrounds.

To cover larger hearth openings, install the optional shroud. At 48 inches wide and just under 38 inches tall, it provides a clean transition between the surround and the existing fireplace.



Cast Iron Surround shown with 20,000 Btu Vent-Free Innsbrook



6 x 7-inch Metal Surround shown with 20,000 Btu Vent-Free Innsbrook



3 x 4-inch Metal Surround shown with 28,000 Btu Vent-Free Loft

Decorative Media for Loft Inserts



Topaz Clear Drops One-inch



Blue Clear Crushed



Onyx Solid Drops One-inch



Clear Frost Crushed



Sangria Luster Droplets 1/2-inch

Black Polished

Crushed



Glacier Ice Droplets 1/2-inch



Bronze Reflective Crushed



Accent Pebbles




Copper Reflective Crushed



Medium Rocks

Minimum Fireplace Opening Dimensions

Model	Α	В	С	D
VFPC20IN	19-3/8	27-1/2	13-1/2	15-3/4
VFPC28IN	22-3/8	30-1/2	15	19
VFLC(10,20)IN	19-3/8	27-1/2	13-1/2	15-3/4
VFLC28IN	22-3/8	30-1/2	15	19



Note: These are the minimum dimensions of a fireplace that the fireplace insert will fit into. It allows room for the box and the fireplace surround to fit onto the front of the unit. It is not intended to be used for framing dimensions.

Gas Inlet			
Type of Gas	Natural or LP		
Iron Pipe Size (N.P.T.)	1/2 inch		
Ignition Systems	Standing Pilot/Piezo or Intermittent Pilot		

Vent-Free Warranty

All Vent-Free products carry a 5-year limited warranty with a 5-year limited labor warranty. All remote controls carry a 1-year limited warranty.

Empire is committed to continuous product improvement; specifications are subject to change without notice. Dimensions in this brochure are approximate; read and follow the framing dimensions in the owners manual supplied with your Empire product. Flame size, shape, and color will vary from photos.



This appliance is design-certified to the ANSI standard by:





SINCE 1932 Empire Comfort Systems Inc. 918 Freeburg Ave. Belleville, IL 62220-2623 info@empirecomfort.com WMH-01035 2/01/19

The Empire Comfort Systems and White Mountain Hearth names and logos are registered U.S. trademarks.