

St. Clair 4300

Features

- Simple Operation
- Easy to Maintain
- EPA 2020 Certified
- Limited Lifetime Warranty
- Multiple Design Options
- Includes Blower

Specifications


- Heating Area 1000-2800 sq. ft.
- Burn Time 10 hours
- Maximum Heat Output 95,000 BTUs
- Maximum Log Length 25 in.
- Firebox Size 4.28 cu. ft.
- Min Fireplace 49 ½" H x 38" W x 27" D


Options & Accessories

- Refractory (Required)
 Classic Brick
 - Faceplate (Required)
 - Traditional Faceplate
 - 2 Door Options (Requires 1)
 - Nickel Door Overlay
 - Black Door Overlay
- Accessories
 - Fresh Air Intake Kit
 - Forced Air Distribution Kit
 - Gravity Air Circulation Kit

St. Clair 4300

DIMENSIONS





MINIMUM FRAMING DIMENSIONS

		Non Combustible
D		B
	C	
	₩	

CT	\sim		10	00
ST.	L	ЯΙΓ	45	00

	А	В	С	D
US	50 3/4″	43 3/8″	26 7/8″	84″

LIMITED LIFETIME: Combustion chamber (welds only) and cast iron door frame, Ceramic Glass, Plating (manufacture defect), step top. LIMITED 7 YEAR: Surrounds, heat shields, ash drawer, pedestal, C-Cast Baffle, secondary air tubes, deflectors and supports. LIMITED 5 YEAR: Handle assembly, glass retainers, air control mechanism, removable carbon steel combustion chamber components. LIMITED 2 YEAR: Standard and optional blower, heat sensors, switches, rheostat, wiring and electronics. LIMITED 1 YEAR: Paint peeling, gaskets, insulation, ceramic fiber blankets, firebricks and other options. LIMITED 90 DAY: All parts replaced under warranty.



info@empirestove.com