



# SPECIFICATION SHEET



## SEBCO 100-300<sup>WATT</sup>

### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- 96 WATT MAX CLASS "2" LISTED OUTPUTS
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

### REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

|                 | CLASS 2           | CLASS 2           | CLASS 2           | CLASS 2           |
|-----------------|-------------------|-------------------|-------------------|-------------------|
| PART NUMBER     | 1111 (100 Watt)   | 1112 (150 Watt)   | 1113 (250 Watt)   | 1124 (300 Watt)   |
| PRIMARY VOLTAGE | 120VAC-1A MAX     | 120VAC-1.4A MAX   | 120VAC-2.3A MAX   | 120VAC-2.75A MAX  |
| OUTPUT VOLTAGE  | 24VAC-4.2A MAX    | 24VAC-6.25A       | 24VAC-10.5A MAX   | 24VAC-12.5A MAX   |
| BREAKERS        | 1x4A              | 2x4A              | 3x4A              | 3x4A              |
| FREQUENCY       | 60 Hz             | 60 Hz             | 60 Hz             | 60 Hz             |
| DIMENSIONS      | 6.75" x 5" x 4.5" |
| WEIGHT          | 10 LBS.           | 10 LBS.           | 13 LBS.           | 13 LBS.           |



# 24 VOLT INSTALLATION DIAGRAM



- H-1 • TO 100V, 120V, 230V, 277V HOT
- H-2 • TO 100V,120V,230V,277V COMMON
- X-1 • 24 VOLT COMMON
- X-4 • CONNECTED BY FACTORY
- 24 VOLT LEAD • HOT

GROUND LUG INCLUDED FOR PRIMARY SIDE INSTALLATION

- PREWIRED TO TRANSFORMER
- 24 VOLT HOT
- 24 VOLT COMMON
- X-1 • 24V COMMON

