


## CSA CERTIFIED-OUTDOOR USE ONLY FOR COMMERCIAL AND RESIDENTIAL USE

KEY VALVE **BRACKET** 




SIDE VIEW

FLEX LINE

**HEARTH PRODUCTS CONTROLS** 2225 LYONS RD. MIAMISBURG, OH 45342 TOLL FREE: 877.585.9800

PHONE: 937.436.9800 www.hpcfire.com



MATERIAL: 304 STAINLESS STEEL

PART NUMBER		DIMENSION CHART				
		PAN	STANDARD BTU		Α"	STND FLEX
PENTA BURNER			PENTA	TORPEDO	Α	LINE LENGTH
TOR-	PENTA13MLFPK-FLEX	13"	65K	65K	45"	36"
TOR-	PENTA19MLFPK-FLEX	19"	65K	65K	45"	36"
TOR-	PENTA25MLFPK-FLEX	25"	65K	65K	54"	36"
TOR-	PENTA31MLFPK- FLEX	31"	65K	65K	54"	36"

<sup>\*</sup>FOR TORPEDO BURNERS ADD TOR-

## NOTES:


- 1. PROPER VENTING
  - ENCLOSURES:
    - For Fire Pit Inserts upto 65K BTU: Required 2 vents, 18 sq.in. each on opposing sides.
  - BOWLS (Copper, concrete or metal) Bowl to be raised above mounting surface minimum of 3/4" gap; Bowl to have a minimum of 6" diameter hole in bottom




- Natural Gas: Supply Pressure: Minimum: 3.5" W.C.; Maximum: 7.0" W.C.
- LP Gas: Supply Pressure: Minimum: 8.0" W.C.; Maximum 11.0" W.C.

IMPORTANT: Ensure any flex line that may be used from the permanent main fuel supply to the product is rated to the stated max btu of the product and certified to ANSI Z21.75\*CSA 6.27.

- 3. MODIFCATION OF PRODUCT WILL VOID ANY CERTIFICATION AND WARRANTY.
- 4. FOLLOW ALL MANUFACTURER INSTALLATION INSTRUCTIONS AND LOCAL CODES.
- 5. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS AS OF THE REVISION DATE.
- 6. DO NOT SCALE DRAWING.
- 7. THESE DRAWINGS ARE FOR SIZING AND PLANNING PURPOSES. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT. THE MANUFACTURER'S RESPONSIBLE FOR THE ACCURACY OF THE DRAWING.
- 8. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info **REFERENCE NUMBER 771-0**





**BRACKET DETAIL** 

771-009