

FDV451

FREE STANDING **DIRECT VENT** GAS STOVE



THE ULTIMATE IN DESIGN, ENGINEERING & QUALITY





A SAFE AND EFFICIENT HEATING APPLIANCE WITH THE CONVENIENCE OF GAS

Model FDV451N Free Standing Direct Vent Gas Stove (Natural Gas), F450FBL Door Front (Charcoal with Black Posts), F451SDSBL Side Doors with Black Frame and Charcoal Solid Panel, Z5GC Bronze Glass (x3), F45LG Log Grate, F451PL Reflective Porcelain Liner, F45FK Fan Kit.

Model
Gas Control
Fuel
Input Low
Input High
FE (P.4.1-15)

FDV451N / NE2 Millivolt / IPI Natural 34,500 BTU 23,750 BTU 65.89% / 67.72% FDV451LP / LPE2 Millivolt / IPI Propane 31,000 BTU 24,500 BTU 72.14% / 74.06%

STANDARD FEATURES*

- Millivolt or IPI valve system allows operation during a power failure with Hi-Low heat and flame adjustment
- Proflame II Models include Remote Control Features flame, fan, thermostat, and smart thermostat (FDV451NE2, FDV451LPE2 Models only).
- Dual burner system, with Realistic Flame Pattern
- · Heat radiating ceramic glass
- Mobile home approved (Direct Vent Model Only)
- Approved for installation in a bedroom or bed sitting room
- Safety Screen Barrier

OPTIONAL FEATURES

Fan Kit

Heat activated with variable speed control

Safety Screen Barrier

Front Color Choices

Charcoal with Accent colors of Flat Black or Stainless Steel

Side Panels

Charcoal Panels with Trim colors of Flat Black or Stainless Steel

Log Sets

Oak

Brick Refractory Liner

Traditional or Herringbone

Reflective Porcelain Liner

Media Types

Bronze Glass or Cannonballs

Thermostat

Wall Mount Millivolt Thermostat or Programmable Thermostat

Remote Control

On/Off, Thermostat On/Off, Thermostat On/Off modulating, Thermostat On/Off modulating and fan control

B-Vent Adapter

Convert Stove to 4" B-Vent



Unit illustrated is a FDV451N Free Standing Direct Vent Gas Stove (Natural Gas), F450FBL Door Front (Charcoal with Black Posts), F451SDSBL Side Doors with Black Frame and Charcoal Solid Panel, Z5GC Bronze Glass (x3), RBCB1 Cannonballs, F45LG Log Grate, F45FK Fan Kit.



Stainless Steel and Flat Black Vent Lid

STYLING









Herringbone Brick Liner RLH


The FDV451 Direct Vent Model provides sealed combustion where it draws outside air for combustion. This model can be vented either horizontally or vertically.

SIZING AND DIMENSIONS





Α	27 ¹ /8"		16 ¹⁵ /16"
В	7"	J	33 ¹ /2"
С	4"	К	20 1/8"
D	20″	L	5 ³ /8"
Ε	26"	М	19 3/4"
F	1 ¹ /4"	Ν	20 5/16"
G	4"	0	⁹ /16"
Н	11 ⁵ /16"	Р	20 5/8"



MINIMUM CLEARANCES TO COMBUSTIBLES:

36" from front of unit $15 \, ^{1}/_{2}$ " from side of unit $2 \, ^{1}/_{2}$ " from back of unit

ALCOVE INSTALLATION:

48" depth (max.) 71 1/2" height (min.) 58" width (min.)



2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: (204) 632-1962 Fax: (204) 632-1960 www.kingsmanfireplaces.com

FDV451

FREE STANDING **DIRECT VENT** GAS STOVE





nts may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification. Industries maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units may be changed at any time without notice or obligation. Certified for USA and Canada to: ANSI 221.88-2017 / CSA 2.33-2017.



Printed in Canada 02/2020 - B087

FOR CALIFORNIA RESIDENTS ONLY:
WARNING! This product can expose you to chemicals including Carbon Monoxide, that is an externally vented by-product of fuel consumption, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.