

CHAMBER SAFE™

U.S. FIREPLACE PRODUCTS



WHY CHAMBER SAFE?

Chamber Safe is a UL Listed, high performance, refractory parging material, designed to strengthen, streamline, and restore the critical smoke chamber area in masonry chimneys. Preferred by chimney professionals, Chamber Safe smooths jagged, corbelled walls typically found in the smoke chamber, and creates a smooth transition between the smoke chamber and flue liner. Chamber Safe is the ideal choice for improving the flow or draft of the fireplace! The unique insulating properties of our Chamber Safe material improves the safety of the chimney by reducing radiant heat transfer through the smoke chamber. This product is non-water soluble.

CHAMBER SAFE FEATURES

- UL LISTED (UL 1777, ORD 2505)
- SUPERIOR ADHESION
- IMPROVES DRAFT
- BETTER WORKABILITY
- ADDS STRUCTURAL STRENGTH
- RESISTS TEMPERATURES UP TO 2500°F
- USE TO REPAIR BRICK, BLOCK, STONE, CLAY FLUES, AND OTHER CLAY PRODUCTS
- DESIGNED FOR PARGE OR CAST APPLICATIONS

CHAMBER SAFE CAN REPAIR:

- FIREBRICK & MASONRY IN SMOKE CHAMBERS
- ASH PITS • CLAY FLUES • FIREBOXES • KILNS
- MASONRY HEATERS • MASONRY OVENS
- MASONRY WALLS • VENT CONNECTIONS
- WOODSTOVES & MORE!

